

KO-2G MSDS

Grey Firm Open Cell

U.S. Department of Labor Occupational Safety and Health Administration

Material Safety Data Sheet

Required Under USDL Safety and Health Regulations for Ship Repairing
Ship Building, and Ship Breaking (29 CFR 1915, 1916, 1917)

Hazardous Ingredients

Paints, Preservatives, & Solvents		Alloys and Metallic Coatings	
Pigments	N/A	Base Metal	N/A
Catalyst	N/A	Alloys	N/A
Vehicle	N/A	Metallic Coatings	N/A
Solvents	N/A	Filler Metal	N/A
Additives	N/A	Others	N/A

Hazardous Mixtures of Other Liquids, Solids, or Gases

- As Kodiak Corporation interprets 29 CFR 1910.1200 this product should not be considered a hazardous material.*
- This product not subject to Sara Title III Section 313.*

Physical Data

Boiling Point (F)	None	Specific Gravity (H2O=1)	1.3 - 1.5
Vapor Pressure (mm Hg.)	None	Percent Volatile Volume (%)	NIL
Vapor Density (AIR =1)	None	Evaporation Rate	-----
Solubility in Water	None	Appearance / Odor	Solid / NIL

Fire and Explosion Hazard Data

Flash Point (Method used)	Ignition Temp. 750F
Extinguishing Media	Any
Special Fire Fighting Procedures	Normal Smoke Protection
Unusual Fire and Explosion Hazards	None

Note: Information herein is based on laboratory test data which is believed to be reliable. However Kodiak Corporation, has no control over the end application of these materials. Therefore, we cannot guarantee that the same results as described herein will be obtained

Note: It is recommended that each user conduct his / her own tests to determine adaptability of these materials to his / her particular application.